

HI-PFLEX 100 GCC CALCIUM CARBONATE

This GCC is surface treated with 1% of Calcium Stearate. This surface treatment enhances the physical properties of a variety of polymeric matrices: Rigid PVC e.g. potable water pipe, DWV, sewer pipe, flexible PVC wire, cable coverings, PVC plastisols, PP compounds etc. Also used as a general filler.

CHEMICAL (Before Treatment):

CaCO ₃		97%
MgCO ₃		0.5%
Fe ₂ O ₃	Less than	0.1%
Moisture	Less than	0.2% @ 110 C

PHYSICAL:

Appearance	Very white powder
Dry Brightness	95 Hunter Y
Specific Gravity	2.7
Density Loose	50 lbs/cu ft
Density Tapped	81 lbs/cu ft
Surface Area	3 m ² /gr
Residue @ 325 mesh	Less than 0.01%
Passing 20 Micron	100%
Passing 10 Micron	80%
Passing 5 Micron	55%
Passing 2 Micron	30%
Passing 1 Micron	15%

PACKING: 50 bags per pallet, 50 lbs net/bag

ORIGIN: INDIA

Admin office: 110 A Block City Center, Nr Idgah Circle Asarwa Bridge, Asarwa, Ahmedabad Gujarat 380 016 **INDIA**

Plant: Plot No. 410 Phase II, Vatva G. I. D. C. Industrial Estate, Vatva, Ahmedabad Gujarat 382 445 **INDIA**

E: inquiry@gmcilt.com **W:** www.gmcilt.com **T:** +91 79905 25617 **F:** +91 79848 07644

Certificate of Incorporation: U24290GJ2019PTC108256 GST NO.: 24AAHCG8288L1ZY

GLOBAL METRO CHEM INDUSTRIES